

# Low Height Flat Cylinders Single Acting Spring Return

700 Kg/Cm<sup>2</sup>

- Flat Jacks incorporate the optimum stroke in the minimum closed height to give lifting force in confined places of work. Strokes being very limited and the area of working being almost inaccessible, mounting bolt holes are provided for positive fixturing.
- Hard chrome plated steel piston rod.
- Stop ring provided on all models.
- Female half coupler & dust cap provided on all models.
- Please contact nearest dealer for cylinders with capacities & strokes not mentioned in the data sheets. All variations are possible on request, subject to confirmation from the dealer.



**CAPACITY 5 TONNE TO 200 TONNE**

**STROKE 5 MM TO 25 MM**

**TYPE OF RAM PLAIN**

MODEL	Capacity		Effective Area cm <sup>2</sup>	VOL cm <sup>3</sup>	Dimension in mm													Approx. Weight kg.	SEAL KIT MODEL
	Tonnes	KN			A	B STROKE	C	D	E	F	G	H	J	K	L	M	N		
XM005005	5	50	7	3.5	36	5	41	60	30	25	5	22	28	105	18	3/8" NPT	41	1	XMSK-5
XM005010				7	41	10	51	60	30	25	5	22	28	105	18	3/8" NPT	41	1	
XM005015				10.6	46	15	61	60	30	25	5	22	28	105	18	3/8" NPT	41	1	
XM005025				17.6	56	25	81	60	30	25	5	22	28	105	18	3/8" NPT	41	2	
XM010005	10	100	14.5	7.2	43	5	48	81	43	38	7	37	37	143	19	3/8" NPT	56	2	XMSK-10
XM010010				14.5	48	10	58	81	43	38	7	37	37	143	19	3/8" NPT	56	3	
XM010015				21.7	53	15	68	81	43	38	7	37	37	143	19	3/8" NPT	56	3	
XM010025				36.2	63	25	88	81	43	38	7	37	37	143	19	3/8" NPT	56	4	
XM020005	20	200	28.2	14.1	51	5	56	100	60	48	10	38	50	162	19	3/8" NPT	76	4	XMSK-20
XM020010				28.2	56	10	66	100	60	48	10	38	50	162	19	3/8" NPT	76	4	
XM020015				42.4	61	15	76	100	60	48	10	38	50	162	19	3/8" NPT	76	4	
XM020025				70.6	71	25	96	100	60	48	10	38	50	162	19	3/8" NPT	76	5	
XM025005	25	250	36.3	18	55	5	60	105	68	53	10	40	51	167	19	3/8" NPT	85	4	XMSK-25
XM025010				36.3	60	10	70	105	68	53	10	40	51	167	19	3/8" NPT	85	5	
XM025015				54.4	65	15	80	105	68	53	10	40	51	167	19	3/8" NPT	85	5	
XM025025				90.7	75	25	100	105	68	53	10	40	51	167	19	3/8" NPT	85	5	
XM030005	30	300	41.8	20.9	57	5	62	115	73	60	11	45	52	177	20	3/8" NPT	95	5	XMSK-30
XM030010				41.8	62	10	72	115	73	60	11	45	52	177	20	3/8" NPT	95	6	
XM030015				62.7	67	15	82	115	73	60	11	45	52	177	20	3/8" NPT	95	6	
XM030025				104.6	77	25	102	115	73	60	11	45	52	177	20	3/8" NPT	95	7	

Suitable handle shall be provided with cylinders whose weight is more than 20 kg.

Note : The right to change any specification without notice is reserved because of constant R&D and product upgradation.

