

- Air Hydraulic Pumps are designed for fast operation, greater versatility and durability.
- Ideal pump where Shop-Floor air is available at 7 bar.
- Carrying handles are of treadle design, which allows easy operation by hand and foot.
- Built in Relief Valve protects hydraulic system components regardless of air pressure.
- Assembly can be done to fit on larger reservoir (if required).
- Provides greater speed at low cost.
- Positive holding even if air pressure turned off .
- It is recommended to attach a Filter-Lubricator unit at air inlet.



MODEL	CP-17012	CP-17100
Air Inlet Pressure	3.5 - 8.5 Bar	3.5 - 8.5 Bar
Max. Oil Pressure	700 Bar	700 Bar
Oil Discharge	0.09 Litre per minute at 700 Bar	0.09 Litre per minute at 700 Bar
Ratio	1 : 100	1 : 100
Reservoir Capacity	1.2 Litre	10 Litre
Useable Oil Capacity	0.8 Litre	8.5 Litre
Oil Outlet Port Size	3/8 " NPT (F)	3/8"NPT (F)
Air Inlet Port Size	1/4" NPT (F)	1/4"NPT (F)
Net Weight Without Oil	9.5 kg	11.5 kg

Note : The right to change any specification without notice is reserved because of constant R&D and product upgradation.

